

|                              |  |
|------------------------------|--|
| <b>Construction</b>          | <ul style="list-style-type: none"> <li>Aluminum, semi-monocoque. 3"x3" main frame tubes plus 2" x 3" rectangular tube on 16" centers- very strong, yet light.</li> <li>Walls and floor: 1/8" (10 gauge) 6061 aircraft/marine aluminum</li> <li>Roof and fenders: the latest in strong, light weight fiberglass technology</li> </ul>   |
| <b>Weight</b>                | <u>Standard Model</u> : Curb weight 2,340 lbs/Tongue weight 260 lbs <u>I Model</u> : Curb 2,440 lbs/Tongue 280 lbs <u>Short Model</u> : Curb 2,175 lbs<br><u>L Model</u> : Curb 2,440 lbs/Tongue 280 lbs <u>LT Model</u> : Curb 2,540 lbs/Tongue 300 lbs   |
| <b>Underside</b>             | Flush, fully-skinned in aluminum to eliminate drag. Rear dolly wheels (not installed on Short Model) eliminate scraping on angled driveways.   |
| <b>Side Doors</b>            | Two front side access doors with quality flush locking handles. Each door - <u>Standard/Short/L Models</u> : 23.5" x 32" <u>I/LT Models</u> : 23.5" x 42"  |
| <b>Rear Opening Size</b>     | <u>Standard</u> Height: 58.5" <u>Short</u> Height: 58.5" <u>I</u> Height: 68.5" <u>L</u> Height: 60" <u>LT</u> Height: 70"    Width: 87"   |
| <b>Heights</b>               | <u>Standard/Short/L Models</u> Exterior 93" (7' 9")/ Interior 68" (5' 8") <u>I/LT Models</u> Exterior 100" (8'4")/Interior 76" (6'4")  |
| <b>Lengths</b>               | <u>Standard/T Models</u> Exterior length: 23' 2" (body 18' 6" + tongue). Interior length for vehicle 199.5" (16' 7.5") from tailgate to front shelf.<br><u>Short Model</u> Exterior: 19' 8" (body 15' 6" + tongue). Interior length for vehicle 164" (13' 8") from tailgate to front shelf.<br><u>L/LT Models</u> Exterior: 24' 6" (body 20' + tongue). Interior length for vehicle 216" (18') from tailgate to front shelf.                     |
| <b>Widths</b>                | Interior Width for vehicle: 80" in-between inner wheel wells. Exterior tire-to-tire width: 102"  |
| <b>Ramp</b>                  | <ul style="list-style-type: none"> <li>Width 87.5" <u>Standard/Short</u> Length 58"    <u>I</u> Length 69"    <u>L</u> Length 60.5"    <u>LT</u> Length 70.5" Spring loaded, lower pivot external springs</li> <li>No cables or loss of head space due to an overhead roller drum with cable springs and side cables</li> <li>See Aerovault website Accessories page for additional extension ramps for low ground clearance vehicles</li> </ul> |
| <b>Floor/Ramp</b>            | Aluminum diamond plate. Ramp/floor height 15" from ground (rear can be lowered during loading by cranking tongue jack up).   |
| <b>Axles</b>                 | Dexter twin 3500lb rubber ride Torflex, EZ lube axles with self-adjusting brakes. No heavy steel sub-frame needed for axles or front coupler.  |
| <b>Brakes</b>                | Integrated electric drum brakes (on all four wheels). Self-adjusting brakes.   |
| <b>Tires; Wheels</b>         | The best... Carlisle N speed-rated (87 mph) radial tires. Five-stud 15" steel wheels, spare included.  |
| <b>Moon Wheel Covers</b>     | Yes those great looking, aerodynamically efficient Moon Discs come standard on every Aerovault.  |
| <b>Spare</b>                 | Included standard is a 15 <sup>th</sup> full-size Carlisle tire and wheel, mounted inside trailer side door for easy access.   |
| <b>Tie Down System</b>       | 4 flush-mount "D" rings in floor to secure car with ratchet tie-downs (see following page for additional tie-down packs).  |
| <b>Loading Aids</b>          | Remote control winch with hard-wired controls AND remote control fob (comes standard!)   |
| <b>Lighting</b>              | Fore and aft interior lights. LED lights in and out. Manual switch turns on white back-up lights on rear of trailer for night work.  |
| <b>Interior Amenities</b>    | <ul style="list-style-type: none"> <li>Aluminum 23" deep shelf in front for storing spare wheels/tires, jack, stands, tools and for track work</li> <li>Four 7.5" wide channels along bottom of walls in front and behind fender wells for easy storage</li> <li>Numerous U-hooks along walls and holes in sides of storage channels so almost anything can be secured anywhere</li> </ul>   |
| <b>Hitch Features</b>        | <ul style="list-style-type: none"> <li>Easy-to-lock heavy duty Bulldog hitch</li> <li>Heavy duty jack (with wheels)</li> <li>Self curling safety cables</li> <li>Breakaway cable</li> </ul>  |
| <b>Venting</b>               | In a special area under the back of the Aerovault's "dorsal" fin, vents allow for a continual exchange of fresh air.   |
| <b>Gross Weight/Payloads</b> | 7,000 lbs gross weight.    Payloads: <u>Standard</u> : 4,670 lbs <u>I</u> : 4,560 lbs <u>Short</u> : 4,825 lbs <u>L</u> : 4,560 lbs <u>LT</u> : 4,460 lbs  |